



★ 产品特点：能承受轴向负载的垫片。




①代号	类型	④材质	硬度 HB	使用温度范围 (°C)
OFAWZ	平头螺栓孔型	高力黄铜+ 固体润滑剂GR1	≥210	-50~150
OFAWTZ	沉头螺栓孔型			



OFAWZ
(平头螺栓孔型)



OFAWTZ
(短头螺栓孔型)



视角标准：第一视角



①代号 - ②规格
OFAWTZ - 20

①代号	②规格	T	D	D ₁	安装孔					倒角		附件										
					P.C.D	数量	OFAWZ		OFAWTZ		a		b									
							平头螺栓	d ₁	d ₂	t												
OFAWZ 平头螺栓孔型 OFAWTZ 沉头螺栓孔型	6	3(4)	6.2	25	15	2	M3	3.5	6	2.4	1.5	0.2										
	8		8.2	28	18																	
	10		10.2	30	20																	
	12		12.2	40	28																	
	13	13.2	50	35	2																	
	15	15.2																				
	16	16.2																				
	18	18.2																				
	20	20.2	5	25.2	55	40																
	25	25.2												60	45	M5	4.5	7.5	3	2.5		
	30	30.2												70	50							
	35	35.2												80	60							
40	40.2	80	60	M6	5.5	9	4	3	0.4	M6x20(2个)												
50	8	50.3	100					75	4		4	0.5										

()内为OFAWTZ的尺寸。



交货期

5天发货



优惠价

数量	1-9	10~
折扣率	100%	现询

