



交叉滚子轴承 外圈分割型

★ 产品特点: 适用于负载较大的场景



代号	类型	后置代码	轴承游隙	轴承精度	轴承材料	
					国标	相当
BDA	外圈分割型	UU(两端密封垫片)	CC0	P5	GCr15	SUJ2
BDB						



视图标准: 第一视角



型号
BDA-RA10008UUCC0P5

代号	型号	公称规格	主要尺寸					肩部尺寸		基本额定负载 (径向)		参考重量 (kg)	
			d	D	B	r (min)	润滑孔		ds (max)	Dh (min)	Cr (动) KN		Co (静) KN
		RB3010UUCC0P5	30	55	10	0.6	2.5	1	37	47	7.35	8.36	0.12
		RB3510UUCC0P5	35	60					41	51.5	7.64	9.12	0.13
		RB4510UUCC0P5	45	70					51	61.5	8.62	11.3	0.17
		RA5008UUCC0P5	50	66	8	0.5	2	0.8	53.5	60.5	5.1	7.19	0.08
		RB5013UUCC0P5		80	13	0.6	2.5	1.6	57	72	16.7	20.9	0.27
		RA6008UUCC0P5	60	76	8	0.5	2	0.8	63.5	70.5	5.68	8.68	0.09
		RB6013UUCC0P5		90	13	0.6	2.5	1.6	67	82	18	24.3	0.3
		RA7008UUCC0P5	70	86	8	0.5	2	0.8	73.5	80.5	5.98	9.8	0.1
		RA8008UUCC0P5		96					8	0.5	2	0.8	83.5
		RA9008UUCC0P5	90	106	16	1	3	1.6	93.5	100.5	6.76	12.4	0.12
		RB9016UUCC0P5		130					16	1	3	1.6	98
		RA10008UUCC0P5	100	116	8	0.5	2	0.8	103.5	110.5	7.15	13.9	0.14
		RB10016UUCC0P5		140	16	1	3.5	1.6	109	129	31.7	48.6	0.83
		RB10020UUCC0P5	150	20	8	0.5	2	0.8	113	133	33.1	50.9	1.45
		RA11008UUCC0P5	126	8					0.5	2	0.8	113.5	120.5
		RB11012UUCC0P5	110	135	12	0.6	2.5	1	117	128	12.5	24.1	0.4
		RB11015UUCC0P5		145	15	3.5	1.6	119	136	23.7	41.5	0.75	
		RB11020UUCC0P5	160	20	1								3.5
		RA12008UUCC0P5	120	136	8	0.5	2	0.8	123.5	130.5	7.84	16.5	0.17
		RB12016UUCC0P5		150	16	0.6	3.5	1.6	127	141	24.2	43.2	0.72
		RB12025UUCC0P5	130	180	25	1.5	2	0.8	133	164	66.9	100	2.62
		RA13008UUCC0P5		146	8	0.5	2	0.8	133.5	140.5	7.94	17.6	0.18
		RB13015UUCC0P5	140	160	15	0.6	3.5	1.6	137	152	25	46.7	0.72
		RB13025UUCC0P5		190	25	1.5	2	0.8	143	174	69.5	107	2.82
		RA14008UUCC0P5	140	156	8	0.5	2	0.8	143.5	150.5	8.33	19.1	0.19
		RB14016UUCC0P5		175	16	1	2.5	1.6	147	162	25.9	50.1	1
		RB14025UUCC0P5	150	200	25	1.5	3.5	2	154	185	74.8	121	2.96
		RA15008UUCC0P5		166	8	0.5	2	0.8	153.5	160.5	8.82	20.6	0.2
		RB15013UUCC0P5	160	180	13	0.6	2.5	1.6	157	172	27	53.5	0.68
		RB15025UUCC0P5		210	25	3.5	2	1.6	164	194	76.8	128	3.16
		RB15030UUCC0P5	170	230	30	1.5	4.5	3	169	211	100	156	5.3
		RA16013UUCC0P5		186	13	0.8	2.5	1.6	165	179	23.3	44.9	0.59
		RB16025UUCC0P5	180	220	25	1.5	3.5	2	173	204	81.7	135	3.14
		RA17013UUCC0P5		196	13	0.8	2.5	1.6	175	189	23.5	46.5	0.64
		RB17020UUCC0P5	190	220	20	1.5	3.5	2	184	198	29	62.1	2.21
		RA18013UUCC0P5		206	13	0.8	2.5	1.6	185	199	24.5	49.8	0.68
		RB18025UUCC0P5	200	240	25	1.5	3.5	2	225	255	84	143	3.44
		RA19013UUCC0P5		216	13	0.8	2.5	1.6	195	209	24.9	51.5	0.69
		RB19025UUCC0P5	210	240	25	1	3.5	1.6	202	222	41.7	82.9	2.99
		RA20013UUCC0P5		226	13	0.8	2.5	1.6	205	219	25.8	54.7	0.71
		RB20025UUCC0P5	220	260	25	3.5	2	2	215	245	84.2	157	4
		RB20030UUCC0P5		280	30	4.5	2	2	221	258	114	200	6.7
		RB20035UUCC0P5	240	295	35	2	5	3	225	270	151	252	9.6
		RB22025UUCC0P5		220	280	25	3.5	2	235	265	92.3	171	4.1
		RB24025UUCC0P5	240	300	3.5				2	256	281	68.3	145
		RB25025UUCC0P5	250	310	30	4.5	3	265	290	69.3	150	5	
		RB25030UUCC0P5		330				30	4.5	3	269	306	126.2
		RB25040UUCC0P5	300	355	40	6	3.5	275	326	195	348	14.8	
		RB30025UUCC0P5		360	25	2.5	3.5	2	315	340	76.3	178	5.9
		RB30040UUCC0P5	350	405	40	6	3.5	326	377	212	409	17.2	
		RB35020UUCC0P5		400	20	3.5	1.6	363	383	54.1	143	3.9	
		RB40035UUCC0P5	400	480	35	5	3	422	459	156	370	14.5	
		RB40040UUCC0P5		510	40	6	3.5	428	479	241	531	23.5	
		RB45025UUCC0P5	450	500	25	1	3.5	464	484	61.7	182	6.6	
		RB50025UUCC0P5	500	550				514	534	65.5	201	7.3	

- ▲ 1kgf=9.8N
- ▲ 不承诺此产品品牌
- ▲ 更多规格请咨询客服



交货期

4天发货