

Contact hazard protection cover

for SV-TS 8 enclosures with NH slimline fuse-switch disconnectors

To cover incoming and outgoing sections and NH slimline fuse-switch disconnectors with the Maxi-PLS busbar system in the rear enclosure section so that they are safe from finger contact (IP 2X).

Material:
Sheet steel


Colour:
RAL 7035

Supply includes:

- 3 front covers
- 2 depth covers
- 2 side covers
- Connector parts

Note:

- SV-TS 8 enclosures, see page 84.
- NH slimline fuse-switch disconnectors, see page 306/307.



For enclosures			Free installation width mm ¹⁾ when using longitudinal connectors			Packs of	Model No. SV	Page
Width mm	Height mm	Depth mm	without	one side	both sides			
600	2000	600	500	450	400	1 set	9660.460	
800	2000	600	700	650	600	1 set	9660.470	
1000	2000	600	900	850	800	1 set	9660.480	
1200	2000	600	1100	1050	1000	1 set	9660.490	

Also required

Mounting bracket ²⁾						24	9660.090	344
--------------------------------	--	--	--	--	--	----	----------	-----

Accessories

Blanking cover for NH slimline disconnectors	Size 00					4	9660.180	344
	Sizes 1 – 3					4	9660.190	344

¹⁾ When using the top-mounted busbars SV 9649.160/SV 9659.160, see page 328.

Longitudinal connectors SV 9640.191/SV 9650.191 for Maxi-PLS busbars, see page 328.

²⁾ 2 mounting brackets are required to attach the contact hazard protection cover plates.