

Climate control accessories

Water distribution

Electric condensate evaporator

For external mounting on enclosures. For use with all cooling units and air/water heat exchangers (wall-mounted). Suitable for international use thanks to multi-voltage support.

Evaporation performance:

- at 230 V: 3.5 l/d
- at 115 V: 3.0 l/d

Colour:

- RAL 7035

Supply includes:

- Electric condensate evaporator, ready to connect

Width mm	Rated operating voltage V, ~, Hz	Model No.
280	115 – 230, 1~, 50/60	3301.500
400	115 – 230, 1~, 50/60	3301.505

Technical details:

Available on the Internet



Condensate collecting bottle

For mounting on the enclosure. For use with all enclosure cooling units and air/water heat exchangers.


- Safety overflow at the side
- Capacity approximately 0.75 l

- 1 Condensate discharge hose
- 2 Membrane grommet
- 3 Max. 70 mm

Packs of	Model No.
1 pc(s).	3301.600

Supply includes:

- Condensate collecting bottle
- Bottle holder
- Assembly parts



Condensate hose

For discharging and transporting condensate. For connection to cooling units and air/water heat exchangers.

Material:

- PVC, transparent

For units	Hose length m	Material thickness Ø mm	Model No.
3201. . . .	5	6 x 1	3301.606
3302. . . .	10	8 x 1.5	3301.608
3212. . . ./3303. . . ./3361. . . .	10	10 x 1.5	3301.610
3209. . . ./ 3210. . . ./3214.100/3215.100/3216.480/3273. . . ./ 3304. . . ./3305. . . ./3328. . . ./3329. . . ./3332. . . ./3359. . . ./ 3363. . . ./3364. . . ./3366. . . ./3373. . . ./3374. . . ./3375. . . ./ 3377. . . ./3378. . . ./3382. . . ./3383. . . ./3384. . . ./3385. . . ./ 3386. . . ./3387. . . .	10	12 x 2	3301.612

